



# WOOD-BOO™ FLOORING

50 Walford Road SW  
 Cedar Rapids, IA 52404  
 319-731-0200 (office)  
 319-848-2181 (fax)  
[www.woodboo.com](http://www.woodboo.com)

## WOOD-BOO-TOO™ SPECIFICATIONS SHEET

**Sizes:** Click: 27.9 sq ft/box approx 55 lbs/box  
 Length: 1'-4' random length: Average length 3'  
 Width: 4 3/4"  
 Thickness: 5/8" 3mm wear layer, 10/5mm Bamboo composite core, 3mm cork underlay

### MSDS: Strand Woven Bamboo Core

**Test:** ASTM-E-648 critical radiant flux  
 Source: HPVA  
 Results: received 1.0 plus, highest rating for Class 1  
**Test:** NVLAP 23/T02 and FTM-1-1983 phenol formaldehyde emissions  
 Source: PSI  
 Results: 0.04 heho (ug/ml), \*0.02 ppm  
**Test:** ASTM D1037-99 sections 108-111, linear variation with change in moisture  
 Source: PSI  
 Results: (@90% RH) parallel 0.15 perpendicular 2.16 thickness 1.39

### Leed Certification Info:

**Credit MR6, Rapidly Renewable Materials:** Bamboo flooring manufacturer's product data for each product used, indicating that product(s) are manufactured from a rapidly renewable resource.  
**Credit EQ 4.1, Low-Emitting Materials:** Adhesives and/or sealants manufacturer's product data.  
**Credit EQ 4.2, Low-Emitting Materials:** Paints and/or coatings manufacturer's product data for field finished floor coatings.

### Sound Transmission Class for Cork Underlayment:

With Cork 3mm (1/8" thick) with wood floating floor, engineered floor		
	STC	IIC
Concrete Slab 8"	54	60
Concrete Slab 6"	52	57
Wood Frame	55	61

With Cork 6mm (1/8" thick) with wood floating floor, engineered floor		
	STC	IIC
Concrete Slab 8"	56	62
Concrete Slab 6"	54	59
Wood Frame	57	63